

TORQUE WRENCH PUMPS — AIR





sd und



X1A1-PT

CLASSIC SERIES AIR HYDRAULIC Torque Wrench Pump

- Use where air is the preferred source of power
- · Powerful 3 hp motor starts under load
- · External adjustable pressure regulator
- · Retract side internal relief valve protects tool
- · Use for double or single acting tools

X1A1-PT

- · Power Team PA55 Base pump unit
- · Two-speed high performance pump
- · Retract side internal relief valve protects tool
- · 4-way 2-position solenoid valve standard
- · Utilizes rugged electrical controls
- · External adjustable pressure regulator
- · Hand remote standard
- · For single or double acting tools

TORQUE WRENCH PUMPS — AIR

Specifications and Dimensional Data







Pump Model	Oil Delivery per min.	Oil Reservoir gal.	Usable Oil in.3	Overall Width in.	Overall Length in.	Overall Height in.	Pump Weight w/0il lbs.
RWP55	465 in³ @ 100 psi 55in³ @ 10,000 psi	2.5	590	16.55	9.5	19.83	98
RWP55-4 (4-tool manifold)	465 in³ @ 100 psi 55in³ @ 10,000 psi	2.5	590	16.55	9.5	19.83	98
X1A1-PT	465 in³ @ 100 psi 55in³ @ 10,000psi	2.5	590	10.75	18	18.75	75.4



HOSES – DUAL LINE				
TWH15	15', 1/4" ID non-conductive			
	4.6m, 9.5mm ID non-conductive			
TWH20	20', 1/4" ID non-conductive			
	6m, 9.5mm ID non-conductive			
TWH50	50', 1/4" ID non-conductive			
	15.2m, 9.5mm ID non-conductive			