

TORQUE WRENCH PUMPS — ELECTRIC





Sd und



X1E1-PT

CLASSIC SERIES HYDRAULIC Torque Wrench Pump

- · Two-speed high performance pump
- External adjustable pressure regulator
- · Retract side internal relief valve protects tool
- · Hand remote
- · Use for double or single acting tools
- Four-tool manifold (-4 model only) allows use of up to four tools simultaneously

X1E1-PT

- · Power Team PE55 Base pump unit
- · Two-speed high performance pump
- $\boldsymbol{\cdot}$ Retract side internal relief valve protects tool
- · 4-way 2-position solenoid valve standard
- · Utilizes rugged electrical controls
- · External adjustable pressure regulator
- Hand remote standard
- · For single or double acting tools

TORQUE WRENCH PUMPS — ELECTRIC

Specifications and Dimensional Data







Pump Model	Oil Delivery per min.	Oil Reservoir gal.	Usable Oil in.3	Overall Width in.	Overall Length in.	Overall Height in.	Pump Weight w/Oil lbs.
PE55TWP PE55TWP-E110* PE55TWP-E220*	704 in ³ @ 100 psi 56 in ³ @ 10,000 psi	2.5	525	17.14	9.5	18.12	75
PE55TWP-4 PE55TWP-4-E110* PE55TWP-4-E110*	704 in ³ @ 100 psi 56 in ³ @ 10,000 psi	2.5	525	18.49	9.5	19.15	78
X1E1-PT	55 in ³ @ 10,000 psi	2.5	525	13.9	13.1	18.1	73

	ELECTRICAL DATA				
	Electric Motor	Electrical Control			
PE55TWP	1-1/8 hp, 12000 rpm 115V, 25 amps	Remote control with 20-foot cord			
PE55TWP-E110*	1-1/8 hp, 12000 rpm 110V/50Hz, 25 amps	Remote control with 20-foot cord			
PE55TWP-E220*	1-1/8 hp, 12000 rpm 220V/50Hz, 13 amps	Remote control with 20-foot cord			
X1E1-PT	1-1/8 hp, 12000 rpm 220V/50Hz, 13 amps	Remote control with 20-foot cord			

^{*} CE Approved-designed for 50Hz. applications.